

**Proudly
Australian**



Empty Cartridge Canisters

The Canisters are designed to meet the market requirements for Refillable Cartridges which can be loaded with various Medias. The Polypropylene construction in combination with different medias make them suitable for a wide range of applications including: pH correction, Chlorine reduction, Hardness removal, Organic Colour and Taste correction, and Deionization.

The Up Flow design of the cartridge ensures maximum contact time with the media for optimum performance and incorporates a Compression pad to discourage channelling. The Canister has a Pre-Filter pad for Sediment removal and a 10 micron Post-Filter to prevent media fines from passing. The base of the canister is threaded for quick and easy media replacement.

Features and Benefits

- Price Competitive
- Simple Installation
- Refillable
- Standard Cartridge Sizes
- Wide Variety of Applications
- Individually Wrapped and Sealed

Typical Applications

(Depending on Media used)

- Post-Reverse Osmosis (RO)
- Battery Water
- Scale Prevention
- pH Correction
- D.I. (Deionization)

General Specifications

- Micron Ratings (Nominal): 10
- **Standard Diameter:**
- Lengths: 250mm (9⁷/₈"
508mm (20")
- Outside Diameter: 73mm (2⁷/₈"
- Inside Diameter: 25mm (1")
- Canister Capacity: (250mm) 0.8 Lts
(508mm) 1.6 Lts
- **Large Diameter:**
- Lengths: 250mm (9⁷/₈"
508mm (20")
- Outside Diameter: 114mm (4¹/₂"
- Inside Diameter: 25mm (1")
- Canister Media Capacity:
(250mm) 2.0 Lts
(508mm) 4.0 Lts
- Temperature Ranges: 4.4°C - 43°C
(40°F - 110°F)

Note:

Capacities and Flow Rates are dependent on the types of Media used.

The Cartridge Canister is supplied Empty.

Warning:

For drinking water applications, do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection.

Series: WCECC



Model No.

COOLABAH WATER

Ah... that's better !

10"

WCECC10S
WCECC10L

20"

WCECC20S
WCECC20L

Cartridge Canister Refillable

Phone
1800 069 800
0269 258 555